






# SDH101616C4

SELF DRILLING HEX 10-16X16MM SCREW - CLASS 4

GALVANISED IN AUSTRALIA

 	<b>COATING</b> CLASS 4 TO AS3566 2002	<b>DRILL RANGE</b>  Drill Range 0.75-3.5mm
<b>SELF DRILLING</b> For fixing to Metal up to 3.5mm Hex Socket 5/16"	<b>BOX QTY</b> <b>1000</b>	
<b>PART NO</b> SDH101616C4	<b>QUICK ORDER CODE</b> <b>F180</b>	
 9 341946 008264		



## APPLICATION

Suitable for use in:

- Steel-to-Steel Framing
- Wall Cladding to Steel Purlins
- Metal-to-Metal applications such as signs and fencing.

Steel Base Material



## FEATURES AND BENEFITS

- 5/16 hex drive - easy to drive in the screw, and the most common head size used for general steel-to-steel applications
- SD drill point - can drill fast and efficiently into 3.5mm of steel with no need for a pre-drilled hole
- Coating - Class 4 Galvanised coating




## INSTALLATION INSTRUCTIONS

- Use a 5/16 hex socket bit
- Use mains, air or cordless screw driver with a speed of up to 3,000rpm
- Fit the socket bit around the screw head and place screws in the fastening position
- Apply consistent firm pressure on the screw driver until the screw has fastened. **DO NOT OVERTIGHTEN.**

\*Appropriate screw gun / drill with torque control and depth gauge adjustment should be used.

## ADAPTER TO USE

Hex Socket 5/16"



## FASTENER PROPERTIES

<b>Material</b>	Carbon Steel 1022	<b>Torsion</b>	9.9Nm	<b>Pull Out Values (G450 Grade Steel)</b>	
<b>Heat Treatment</b>	To AS3566	<b>Single Shear</b>	6.7kN	<b>1.5mm</b>	3.614kN
<b>Coating</b>	Class 4 Galvanised				