



SDH121420C4

SELF DRILLING HEX 12-14X20MM SCREW - CLASS 4

GALVANISED IN AUSTRALIA

	COATING	DRILL RANGE
	CLASS 4 TO AS3566 2002	 Drill Range 1-4.5mm
SELF DRILLING For fixing to Metal up to 4.5mm Hex Socket 5/16"	BOX QTY	
PART NO SDH121420C4	1000	
 9 341946 008264		QUICK ORDER CODE F190



APPLICATION

Suitable for use in:

- Steel Wall Framing
- Steel Trusses
- Cladding and general fixing of metal-to-metal.

Steel Base Material



FEATURES AND BENEFITS

- 5/16 hex drive - easy to drive in the screw, and the most common head size for steel to steel applications
- SD drill point - can drill fast and efficiently into up to 4.5mm of steel with no need for a pre-drilled hole
- Coating - Class 4 Galvanised coating




INSTALLATION INSTRUCTIONS

- Use a 5/16 Hex Socket Bit
- Use mains, air or cordless screw driver with a speed of up to 2,500rpm
- Fit the socket bit around the screw head and place the screws in the fastening position
- Apply consistent firm pressure on the screw driver until the screw has fastened. **DO NOT OVERTIGHTEN.**

ADAPTER TO USE

Hex Socket 5/16"



*Appropriate screw gun / drill with torque control and depth gauge adjustment should be used.



FASTENER PROPERTIES

Material	Carbon Steel 1022	Torsion	14.02Nm	Pull Out Values (G450 Grade Steel)
Heat Treatment	To AS3566	Single Shear	9.67kN	1.5mm 4.42kN
Coating	Class 4 Galvanised			