






SDH141042C4

SELF DRILLING HEX 14-10X42MM SCREWS CLASS 4

GALVANISED IN AUSTRALIA

 	COATING CLASS 4 TO AS3566 2002	DRILL RANGE  Drill Range 1.0-5.0mm
SELF DRILLING For general use in steel to steel applications 3/8 Hex	BOX QTY 1000	
PART NO SDH141042C4		
 9 341946 008332		QUICK ORDER CODE F225



APPLICATION

Screws can be used in general Metal to Metal applications.

Steel Base Material



FEATURES AND BENEFITS

- 3/8 Hex Drive - Easy to drive in the screw
- SD drill point - Can drill fast and efficiently with no need for a pre drilled hole into up to 5mm of steel
- Coating - Class 4 Galvanised coating




INSTALLATION INSTRUCTIONS

- Use a 3/8 Hex Socket Bit
- Use mains, Air or Cordless Screw Driver with a speed of up to 3,000rpm
- Fit the 3/8 Hex Socket Bit around the screw head and place screws in the fastening position
- Apply consistent firm pressure on the screw until the screw is fastened.
DO NOT OVERTIGHTEN.

ADAPTER TO USE

Hex Socket 3/8"



FASTENER PROPERTIES

Material	Carbon Steel 1022	Torsion	20.49Nm	Pull Out Values (G450 Grade Steel)
Heat Treatment	To AS3566	Single Shear	10.24kN	1.6mm 3.88kN
Coating	Class 4 Galvanised			